



ECCTS5244CV20

Controller con ricevente integrata a 4 canali in tensione costante per RGB/RGBW

- da ordinare in aggiunta all'alimentatore
- da abbinare a TOUCH02L1, TOUCH03L1, ECPNL2301DM20 o ECCTR1244CV20

Generale

Tipo	controller a tensione costante Radio Frequenza
Lunghezza (mm)	175
Larghezza (mm)	44
Altezza (mm)	30
Colore	bianco
Materiale	PC
Montaggio	a superficie
Peso (g)	150

Elettronica

Alimentazione	DC
Input	5 ~ 24V DC
Output	5 ~ 24 V DC
Output Corrente per canale	max 5 A
Output Corrente totale	20 A
Output Potenza	240W @ 12V, 480W @ 24V
Power Supply	N/A
Uscite	4

Lighting

Color Range	RGBW
-------------	------

Controllo

Segnale in uscita	PWM-CV
Controllo	Radio Frequenza
Numero di canali	4

Caratteristiche generali

Temperatura di utilizzo	-30 ~ +55 °C
Grado IP	IP20



ECCTS5244CV20

RGB/RGBW controller with integrated 4-channel receiver constant voltage

- order in addition to PSU

- suitable only for TOUCH02L1, TOUCH03L1, ECPNL2301DM20 or ECCTR1244CV20

General

Product Type	Constant Voltage Driver, Wireless
Length (mm)	175
Width (mm)	44
Height (mm)	30
Housing Color	White
Housing Material	PC
Mounting	Surface mounted
Weight (g)	150

Electronics

Input Domain	DC
Input Voltage	5 ~ 24V DC
Output Voltage	5 ~ 24 V DC
Output Current per output	max 5 A
Output Current Max. (A)	20 A
Output Power (W)	240W @ 12V, 480W @ 24V

Power Supply	N/A
LED Outputs	(max mA)5000

Lighting

Color Range	RGBW
-------------	------

Control

Output Signal	PWM-CV
Control	Radio Frequency
Number of channels	4

Environmental

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP20

CE IP20