



## ECPNL2301DM20

### LED Touch Controller DMX/RF/WIFI RGBW a 4 zone

- da abbinare a ECCTS1284CC20, ECCTS5244CV20 o a dispositivi controllati con bus DMX512

rev 01 - 06/07/21

#### Generale

|                |                       |
|----------------|-----------------------|
| Tipo           | Controller, Wireless  |
| Lunghezza (mm) | 86                    |
| Larghezza (mm) | 86                    |
| Altezza (mm)   | 36                    |
| Colore         | Bianco                |
| Materiale      | PC                    |
| Montaggio      | su scatola da incasso |
| Peso (g)       | 225                   |

#### Elettronica

|               |             |
|---------------|-------------|
| Alimentazione | AC          |
| Input         | 115-230 Vac |

#### Lighting

|                 |      |
|-----------------|------|
| Range di colori | RGBW |
|-----------------|------|

#### Control

|                         |                      |
|-------------------------|----------------------|
| Segnale in uscita       | DMX, RF              |
| Controllo               | Radio Frequenza, DMX |
| Range di dimmerazione   | 0~100%               |
| Curva di dimming        | Lineare              |
| Modalita' di gestione   | Touch pannel         |
| Portata Radio Frequenza | 100m                 |
| Zone                    | 4                    |
| Funzioni                | programmabile        |

#### Protezioni

|                      |    |
|----------------------|----|
| Inversione polarita' | si |
| Sovraccarico         | si |

#### Caratteristiche generali

|                         |              |
|-------------------------|--------------|
| Temperatura di utilizzo | -30 ~ +55 °C |
| Grado IP                | IP20         |



## ECPNL2301DM20

### LED Touch Controller DMX/RF/WIFI RGBW

#### 4 zones

- suitable only for ECCTS1284CC20, ECCTS5244CV20 or devices DMX512 controlled

#### General

|                  |                      |
|------------------|----------------------|
| Product Type     | Controller, Wireless |
| Length (mm)      | 86                   |
| Width (mm)       | 86                   |
| Height (mm)      | 36                   |
| Housing Color    | White                |
| Housing Material | PC                   |
| Mounting         | Built-in             |
| Weight (g)       | 225                  |

#### Electronics

|               |             |
|---------------|-------------|
| Input Domain  | AC          |
| Input Voltage | 115-230 Vac |

#### Lighting

|             |      |
|-------------|------|
| Color Range | RGBW |
|-------------|------|

#### Control

|                      |                      |
|----------------------|----------------------|
| Output Signal        | DMX, RF              |
| Control              | Radio Frequency, DMX |
| Dimming Range        | 0~100%               |
| Dimming Curve        | Linear               |
| Driver Configuration | Touch Panel          |
| Remote Distance      | 100m                 |
| Zones                | 4                    |
| Functions            | programmable         |

#### Protection

|                  |     |
|------------------|-----|
| Reverse Polarity | Yes |
| Overload         | Yes |

#### Environmental

|                       |              |
|-----------------------|--------------|
| Operating Temperature | -30 ~ +55 °C |
| Ingress Protection    | IP20         |