

# INDOOR UPLIGHT ORIENTATION LIGHT



## SIMPLY 1.0

Ø 40 mm  
H 10 mm

Ø 28 mm

CE EAC LED TECH III kg 0.03 IP44  
A A+ A++ CASAMBI T max 40°C

### POWER / POWER SUPPLY CODE

max 1W max 250mA  
**SM1011** **D C** Chrome  
**SM1011** **D P** Pearl chrome

### LED COLOUR

**F** - 2700K  
**5** - 3000K  
**9** - 4000K  
**0** - 5000K  
**1** - blue

### OPTICS

diffuse

LUMEN OUTPUT AT SOURCE 75 lm (3000K, 250mA)

DELIVERED LUMEN OUTPUT 37 lm (3000K, 250mA)

NO. AND TYPE OF LED 1 power LED  
1/4 ANSI BIN (white LED colour)  
50000h L95 B10 (Ta 25°C)

MATERIAL body and trim in anodized aluminium  
screen in opal polycarbonate

POWER SUPPLY UNIT not included, see p. 904

POWER CABLES includes 2x0.30 m single-core cables

WIRING series

MOUNTING recessed (ceiling, wall, floor)

PHOTOMETRIC DATA see p. 873



Chrome



Pearl chrome

< **SIMPLY 1.0**  
3000K, 1W, pearl chrome

Project and light planning by / DVDV Studio architetti  
Photo by / Alessio Tamborini  
Private residence, Milan, Italy

## INDOOR STEP LIGHTS

### SIMPLY 1.0

D - Diffuse

