L&L


DATASHEET

Made in Italy



Combina D 3.0, code: CC3020100090L0 Recessed for indoor applications

C E 岩 E 配 🐵 🗠 0,90 kg IP40 IP44 with filter 🙂 〒 CASAMBI 🖅



DESCRIPTION

recessed downlight for indoor applications; recessed (ceiling); Power consumption: max 15W; Power supply: max 400mA; Lumen output at source: 1349 lm (3000K, 400mA, CRI >90); Delivered lumen output: 1094 lm (3000K, 400mA, 36°, CRI >90); 1 power LED High Intensity, 2-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 4000K; Optics: 36°: optical system consisting of a deep-set, high-efficiency TIR lens; CRI Colour Rendering Index: >90; Body material: body made of low-copper-content die-cast aluminium alloy EN AB 46100, for excellent corrosion resistance, and flameretardant Bayblend. Trim and cover made of low-copper-content die-cast aluminium alloy EN AB 46100 for excellent resistance to corrosion; RAL finish on request; power supply unit not included; Wiring: series; includes 2x0.30 m single-core PVC cables; Control system: dimming via dimmable driver: Ingress protection; IP40, IP44 with filter; UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover; Easy to wire. The electrical cables can be attached directly to the connector, making the product easier to install; Casambi control using the Casambi app with dedicated electronics; Operating temperature: 0°C - +45°C; Appliance class: class III; Weight: 900 gr; Dimensions: ø136 mm / 136x136 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WGCC30A1F Round bezel, WGCC30A1T Round bezel, WGCC30A2F Square bezel, WGCC30A2T Square bezel, WHCC30A1 Honeycomb louvre, WRCC30R1D Diffuser filter, WRCC30R1T Transparent IP44 screen, WRCC30R1W Elliptical filter, WZCC30108 Flat, round cover, WZCC3010E Flat, round cover, WZCC3010N Flat, round cover, WZCC3010Z Flat, round cover, WZCC30208 Flat, square cover, WZCC3020E Flat, square cover, WZCC3020N Flat, square cover, WZCC3020Z Flat, square cover, WZCC30308 Shallow, round cover, WZCC3030E Shallow, round cover, WZCC3030N Shallow, round cover, WZCC3030Z Shallow, round cover, WZCC30408 Shallow, square cover, WZCC3040E Shallow, square cover, WZCC3040N Shallow, square cover, WZCC3040Z Shallow, square cover, WZCC30508 Deep, round cover, WZCC3050E Deep, round cover, WZCC3050N Deep, round cover, WZCC3050Z Deep, round cover, WZCC30608 Deep, square cover, WZCC3060E Deep, square cover, WZCC3060N Deep, square cover, WZCC3060Z Deep, square cover; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

9/05/2024 Rev. 44

DATASHEET

TECHNICAL DATA



ELECTRICAL CHARACTERISTICS	
Power consumption	max 15W
Power supply	max 400mA
Power supply unit	power supply unit not included
Control system	dimming via dimmable driver
Wiring	series
LIGHTING CHARACTERISTICS	
Number and type of LED	1 power LED High Intensity
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	4000K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	36°
Lumen output at source	1349 lm (3000K, 400mA, CRI >90)
Delivered lumen output	1094 lm (3000K, 400mA, 36°, CRI >90)
MECHANICAL CHARACTERISTICS	
Dimensions	ø136 mm / 136x136 mm
Weight	900 gr
Body material	body in die-cast aluminium and Bayblend, bezel and cover in die-cast aluminium
GENERAL CHARACTERISTICS	
Ingress protection	IP40, IP44 with filter
Operating temperature	0°C - +45°C
Features	UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 2x0.30 m single-core PVC cables
Notes	Easy to wire. The electrical cables can be attached directly to the connector, making the product easier to install; Casambi control using the Casambi app with dedicated electronics




PHOTOMETRIC DATA

 ${\rm L}$ - 36° CRI 90 flat, round cover

		Lux max (3000K)	cd/Klm max 2538	— C0 - C180
H (m)	Ø (m)		HAN	XXX
1,00	0,65	2776		
2,00	1,30	694		
3,00	1,95	308		
4,00	2,60	174	30°	30°
5,00	3,25	111	0°	50

L - 36° CRI 90 shallow, round cover



L - 36° CRI 90 deep, round cover

		Lux max (3000K)	cd/Klm max 2374	- C0 - C180
H (m)	Ø (m)		HAN	XXX
1,00	0,65	2797		
2,00	1,30	699		
3,00	1,95	311	\wedge	\sum
4,00	2,60	175	30°	30°
5,00	3,24	112	0°	50

ACCESSORIES

Installation Accessories



WGCC30A1F Round bezel for installation flush with ceiling Required installation accessories, not included



L - 36° CRI 90 flat, square cover

		Lux max (3000K)	cd/Klm max 2538	— C0 - C180
H (m)	Ø (m)		HAN	AH .
1,00	0,64	2776		
2,00	1,28	694		\sum
3,00	1,92	308	\wedge	TX
4,00	2,57	174	30°	30°
5,00	3,21	111	0°	50

L - 36° CRI 90 shallow, square cover

		Lux max (3000K)	cd/Klm max 2538	— C0 - C180
H (m)	Ø (m)		HAN	AH .
1,00	0,64	2776		
2,00	1,28	694		\sum
3,00	1,92	308	\wedge	$T \rightarrow$
4,00	2,57	174	30°	30°
5,00	3,21	111	0°	50

L - 36° CRI 90 deep, square cover

		Lux max (3000K)	cd/Klm max 2374	— C0 - C180
H (m)	Ø (m)		HAN	AH
1,00	0,64	2795		
2,00	1,28	699		1×2
3,00	1,92	311	\wedge	$T \rightarrow$
4,00	2,56	175	30°	30°
5,00	3,20	112	0°	50



WGCC30A1T Round bezel for rebated installation Required installation accessories, not included



5,00 3,20

COMBINA D 3.0, CODE: CC3020100090L0



WGCC30A2F

Square bezel for installation flush with ceiling Required installation accessories, not included



WZCC30108

Flat, round cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included

The paints that can be used on primed lighting fixtures are the same

ones that are suitable for use on masonry surfaces, i.e: two-pack



Square bezel for rebated installation Required installation accessories, not included



WZCC3010E Flat, round cover

white Required installation accessories, not included



WZCC3010N Flat, round cover black Required installation accessories, not included



WZCC3010Z Flat, round cover antique bronze Required installation accessories, not included



WZCC30208

primer

Flat, square cover



WZCC3020E Flat, square cover white Required installation accessories, not included



WZCC3020N Flat, square cover black Required installation accessories, not included

polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC3020Z Flat, square cover antique bronze Required installation accessories, not included

COMBINA D 3.0, CODE: CC3020100090L0





WZCC30308 Shallow, round cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC3030E Shallow, round cover white Required installation accessories, not included



WZCC3030N Shallow, round cover black Required installation accessories, not included





WZCC3030Z Shallow, round cover antique bronze Required installation accessories, not included



WZCC30408 Shallow, square cover

primer The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included WZCC3040E Shallow, square cover white Required installation accessories, not included



WZCC3040N Shallow, square cover black Required installation accessories, not included



WZCC30508 Deep, round cover primer



WZCC3040Z Shallow, square cover antique bronze Required installation accessories, not included



WZCC3050E Deep, round cover white




The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included

WZCC3050N Deep, round cover black Required installation accessories, not included



WZCC30608 Deep, square cover primer The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included





WZCC3050Z Deep, round cover antique bronze Required installation accessories, not included



WZCC3060E Deep, square cover white Required installation accessories, not included



WZCC3060N Deep, square cover black Required installation accessories, not included

Anti-glare



WHCC30A1 Honeycomb louvre round and square covers: flat, shallow

Optical Accessories





```
WZCC3060Z
Deep, square cover
antique bronze
Required installation accessories, not included
```



COMBINA D 3.0, CODE: CC3020100090L0



WRCC30R1D Diffuser filter round and square covers: flat, shallow

WRCC30R1W

Elliptical filter Adding the filter changes the light output: please consult the photometric data.

round and square covers: flat, shallow

Other

WRCC30R1T Transparent IP44 screen round and square covers: flat, shallow

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.