Made in Italy

16/11/2026 Rev. 13/2024


Bright 1.B, code: CB1B0005R6TI-1

Step lights for outdoor applications

kg 500 - kN 5 kg 0,20 IP65 IP68 IK10

T max 50°C






DESCRIPTION


step light for outdoor applications (not suitable for use in immersion in swimming pools or fountains); walkover up to 500 kg; recessed (wall, floor); Power consumption: 2,5W; Power supply: 24Vdc; Lumen output at source: 171 lm (3000K, 2.5W); Delivered lumen output: 38 lm (3000K, 4x60°, 2.5W); 1 power LED, 1/4 ANSI BIN, 50 000h L90 B10 (Ta 25°C); LED colour: 3000K; Optics: radial 1x180°: optical system, with silicone optics for durability, that in combination with the trim enables the creation of a single 180° light beam; Upward flux fraction: 32,83% (1x60°, 2x60°, 3x60°, 4x60°), 28,34% (1x120°), 30,63% (1x180°); CRI Colour Rendering Index: 80; Body material: body made of AISI 316L stainless steel, made on a CNC lathe. Head in AISI 316L stainless steel machined and finished with a special AC19® treatment developed by Luce&Light, to guarantee excellent corrosion resistance of more than 2000 hours of salt spray; Finishes: stainless steel; RAL finish on request; Seals: the silicone rubber gaskets guarantee maximum resistance to UV rays and unchanging mechanical characteristics over time; Thickness of installation surface: min 5 mm, max 30 mm; power supply unit not included; includes 5 m neoprene cable, H05RN-F 2x0,35/0,75 Ø6,3 mm; Ingress protection: IP65, IP68; Impact resistance: IK10; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; Operating temperature: -20°C — +45°C; Maximum device temperature: 50°C (Ta 25°C); Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 200 g; Dimensions: Ø39x63 mm; Cutout dimensions: Ø30 mm; Volume of thermal heatsink: Ø80x100 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WC0202 Outer casing; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

ELECTRICAL CHARACTERISTICS	
Power consumption	2,5W
Power supply	24Vdc
Power supply unit	power supply unit not included
LIGHTING CHARACTERISTICS	
Number and type of LED	1 power LED
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	80
Binning	1/4 ANSI BIN
Optics	radial 1x180°
Lumen output at source	171 lm (3000K, 2.5W)
Delivered lumen output	38 lm (3000K, 4x60°, 2.5W)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø39x63 mm
Weight	200 g
Finishes	stainless steel
Mounting	with outer casing
Body material	body in AISI 316L stainless steel and trim in AISI 316L stainless steel with a special AC19® treatment developed by Luce&Light
Cutout dimensions	Ø30 mm
Volume of thermal heatsink	Ø80x100 mm
GENERAL CHARACTERISTICS	
Ingress protection	IP65, IP68
Operating temperature	-20°C — +45°C
Impact resistance	IK10
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Maximum device temperature	50°C (Ta 25°C)
Appliance class	class III
Drive-over	no
Walkover	up to 500 kg
Power cables	includes 5 m neoprene cable, H05RN-F 2x0,35/0,75 Ø6,3 mm
Protection systems	IPS (Intelligent Protection System)
Photobiological safety	in accordance with IEC TR 62778:2014

PHOTOMETRIC DATA






1x180°

ACCESSORIES

Installation Accessories



WC0202
Outer casing

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.