





Made in Italy



03/11/2025 Rev. 14/2024







DESCRIPTION

projector for outdoor applications; surface mounted (ceiling, wall, ground, spike); Power consumption: 15W; Power supply: 24Vdc; Lumen output at source: 1343 lm (3000K, 15W, CRI >90); Delivered lumen output: 945 lm (3000K, 42°, 15W, CRI >90); 1 high power density COB LED, 2-step MacAdam, 50 000h L95 B10 (Ta 25°C); LED colour: 2700K; Optics: 42°: optical system consisting of a high-efficiency TIR lens; CRI Colour Rendering Index: >90; Body material: body made of ANTICORODAL 6082 low-copper-content aluminium alloy for excellent resistance to corrosion, made entirely on a CNC lathe. Bracket in AISI 316L stainless steel, tumble finished and painted; Finishes: anthracite finish obtained through an initial treatment with a ceramic nanoparticle coating, to prepare for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1500 hours of salt spray. Paints compliant with the Qualicoat standard used in the automotive sector; RAL finish on request; Screen material: 4-mm-thick transparent extra-clear glass, with high transmittance to ensure chromatic uniformity of light and tempered for excellent resistance to knocks and scratches, with RAL 7015 grey vitrified serigraphy around the edge; power supply unit not included; includes 1.5 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm; Ingress protection: IP66, IP69; Impact resistance: IK09; 12°x64°, 28°x72° optics and shadoweffect filter, adjustable through 360° using the magnet provided; version with bracket in customized height available on request; version in brass available on request; Casambi control using the Casambi app with dedicated electronics; Protection systems; IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; Operating temperature: -20°C - +45°C; Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 1250 g, stainless steel: 2405 g; Dimensions: Ø84x88 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WB8010H Standard snoot - anthracite, WB8020H Asymmetrical snoot anthracite, WH8000 Honeycomb louvre, WP0100 Spike for in-ground installation, WP1004 Fastener strap - 5 m, WP1006H Spike for in-ground installation - h 500 mm - anthracite, WP1007H Spike for in-ground installation - h 800 mm - anthracite; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

DATASHEET TECHNICAL DATA



ELECTRICAL CHARACTERISTICS	
Power consumption	15W
Power supply	24Vdc
Power supply unit	power supply unit not included
117	power supply unit not included
LIGHTING CHARACTERISTICS	4111
Number and type of LED	1 high power density COB LED
Average LED life	50 000h L95 B10 (Ta 25°C)
LED colour	2700K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	42°
Lumen output at source	1343 lm (3000K, 15W, CRI >90)
Delivered lumen output	945 lm (3000K, 42°, 15W, CRI >90)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø84x88 mm
Weight	1250 g, stainless steel: 2405 g
Finishes	anthracite
Mounting	with bracket, screws and plugs
Body material	body in anticorodal aluminium, AISI 316L stainless steel bracket
Screen material	screen in serigraphed-grey and transparent, tempered extra-clear glass
GENERAL CHARACTERISTICS	
Ingress protection	IP66, IP69
Operating temperature	-20°C — +45°C
Impact resistance	IK09
Features	12°x64°, 28°x72° optics and shadow-effect filter, adjustable through 360° using the magnet provided
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 1.5 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm
Protection systems	IPS (Intelligent Protection System)
Photobiological safety	in accordance with IEC TR 62778:2014
Notes	version with bracket in customized height available on request; version in brass available on request; Casambi control using the Casambi app with dedicated electronics

Spike for in-ground installation - h 500 mm - anthracite

PHOTOMETRIC DATA AND ACCESSORIES



PHOTOMETRIC DATA

L - 42° CRI 80

		Lux max (3000K) cd/Klm max 1905 — C0 - C180
H (m)	Ø (m)	15W
1.00	0.77	2213
2.00	1.55	553
3.00	2.32	246
4.00	3.10	138 300
5.00	3.87	89 0°

ACCESSORIES

Installation Accessories









WP1007H

Spike for in-ground installation - h 800 mm - anthracite

Anti-glare



WB8010H

Standard snoot - anthracite



WP1006H

WB8020H

Asymmetrical snoot - anthracite



WH8000

Honeycomb louvre built into the lighting fixture

DATASHEET

GINKO 3.0, CODE: GN30011FLH

PHOTOMETRIC DATA AND ACCESSORIES



The honeycomb louvre can be fitted on all optics, except for 8° , 48° sharp, $12^\circ x64^\circ$, $28^\circ x72^\circ$ optics Order together with the lighting fixture

Other



WP1004 Fastener strap - 5 m

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.