

Made in Italy



11/11/2025 Rev. 11/202





#### DESCRIPTION

projector for outdoor applications; surface mounted (ceiling, wall, ground, spike); Power consumption: 7W; Power supply: 24Vdc; Lumen output at source: 657 lm (3000K, CRI 80); Delivered lumen output: 122 lm (3000K, 36°, CRI 80); 1 high-intensity power LED, 3-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 2700K; Optics: optical range 9°-36°: optical system consisting of a plano-convex lens combined with a high-quality technical filter, adjustable with a mechanical focusing system for extreme flexibility of choice of light emission; CRI Colour Rendering Index: 80; Body material: body made of ANTICORODAL 6082 low-copper-content aluminium alloy for excellent resistance to corrosion, made entirely on a CNC lathe. Zoom ring made of ANTICORODAL 6082, sandblasted and electro-coloured black, and serigraphed with graduations. Bracket in AISI 316L stainless steel, tumble finished and painted: Finishes; anthracite finish obtained through an initial treatment with a ceramic nanoparticle coating, to prepare for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1500 hours of salt spray. Paints compliant with the Qualicoat standard used in the automotive sector; RAL finish on request; Screen material: 4-mm-thick transparent extra-clear glass, with high transmittance to ensure chromatic uniformity of light and tempered for excellent resistance to knocks and scratches, with RAL 7015 grey vitrified serigraphy around the edge; power supply unit not included; includes 1.5 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm; Ingress protection: IP66; Impact resistance: IK07; Casambi control using the Casambi app with dedicated electronics; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; The PID (Protective Impedance Device) protects lighting fixtures from electrical phenomena external to the system, such as static electricity accumulation or electromagnetic interference coming from the mains power. Generally, these are events with a low energy content; Operating temperature: -20°C - +45°C; Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 450 g; Dimensions: Ø54x83 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WF3301 Flexible cable-protection tube - 15 cm, WP0100 Spike for in-ground installation, WP1004 Fastener strap - 5 m, WP1006H Spike for in-ground installation - h 500 mm - anthracite, WP1007H Spike for in-ground installation - h 800 mm anthracite; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

# DATASHEET TECHNICAL DATA



ELECTRICAL CHARACTERISTICS	
Power consumption	7W
Power supply	24Vdc
Power supply unit	power supply unit not included
LIGHTING CHARACTERISTICS	
Number and type of LED	1 high-intensity power LED
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	2700K
CRI Colour Rendering Index	80
Binning	3-step MacAdam
Optics	optical range 9° – 36°
Lumen output at source	657 lm (3000K, CRI 80)
Delivered lumen output	122 lm (3000K, 36°, CRI 80)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø54x83 mm
Weight	450 g
Finishes	anthracite
Mounting	with bracket, screws and plugs
Body material	body in anticorodal aluminium, AISI 316L stainless steel bracket
Screen material	screen in serigraphed-grey and transparent, tempered extra-clear glass
GENERAL CHARACTERISTICS	
Ingress protection	IP66
Operating temperature	-20°C — +45°C
Impact resistance	IK07
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 1.5 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm
Protection systems	IPS (Intelligent Protection System); PID (Protective Impedance Device)
Photobiological safety	in accordance with IEC TR 62778:2014
Notes	Casambi control using the Casambi app with dedicated electronics


# GINKO 2.4, CODE: GN24010FR1H

# PHOTOMETRIC DATA AND ACCESSORIES



# PHOTOMETRIC DATA

R1 zoom - 9° (9° - 36°) CRI 80



R1 zoom - 36° (9° - 36°) CRI 80


			Lux max (3000K)	cd/Klm max 3652	— C0 - C180
H (m)	Ø (m)	Ø (m)	7W	1+1	H
1.00	0.65	0.65	446		
2.00	1.31	1.31	111		
3.00	1.96	1.96	50		
4.00	2.61	2.61	28	30°	30°
5.00	3.26	3.26	18	0°	

# **ACCESSORIES**

# Installation Accessories







#### WP0100

Spike for in-ground installation



#### WP1006H

Spike for in-ground installation - h 500 mm - anthracite

#### WP1007H

Spike for in-ground installation - h 800 mm - anthracite

#### Other





#### WF3301

Flexible cable-protection tube - 15 cm Order together with the lighting fixture

# WP1004

Fastener strap - 5 m

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.