




Made in Italy



04/12/2025 Rev. 09/2024








(€ ĽK [f][⊕ ⊕ △ 0,50 kg IP40 IP44 with filter **♥ 7 (! F)**











DESCRIPTION

recessed downlight for indoor applications; recessed (ceiling); Power consumption: max 11W; Power supply: max 300mA; Lumen output at source: 960 lm (3000K, 300mA, CRI >90); Delivered lumen output: 756 lm (3000K, 300mA, 36°, CRI >90); 1 power LED High Intensity, 2-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 4000K; Optics: 36°: optical system consisting of a deep-set, high-efficiency TIR lens; CRI Colour Rendering Index: >90; Body material: body made of low-copper-content die-cast aluminium alloy EN AB 46100, for excellent corrosion resistance, and flameretardant Bayblend. Trim and cover made of low-copper-content die-cast aluminium alloy EN AB 46100 for excellent resistance to corrosion; RAL finish on request; power supply unit not included; Wiring: series; includes 2x0.30 m single-core cables; Control system: dimming via dimmable driver; Ingress protection: IP40, IP44 with filter: UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover; Easy to wire. The electrical cables can be attached directly to the connector, making the product easier to install; Casambi control using the Casambi app with dedicated electronics; Operating temperature: 0°C - +45°C; Appliance class: class III; Weight: 500 gr; Dimensions: ø85 mm / 85x85 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WGCC20A1F Round bezel, WGCC20A1T Round bezel, WGCC20A2F Square bezel, WGCC20A2T Square bezel, WHCC20A1 Honeycomb louvre, WHCC20A2 Honeycomb louvre, WRCC20R1D Diffuser filter, WRCC20R1T Transparent IP44 screen, WRCC20R1W Elliptical filter, WRCC20S1D Diffuser filter, WRCC20S1T Transparent IP44 screen, WRCC20S1W Elliptical filter, WZCC20108 Flat, round cover, WZCC2010E Flat, round cover, WZCC2010N Flat, round cover, WZCC2010Z Flat, round cover, WZCC20208 Flat, square cover, WZCC2020E Flat, square cover, WZCC2020N Flat, square cover, WZCC2020Z Flat, square cover, WZCC2020N Flat, square cover, WZCC2020X Flat, square cover, wzc2020X Flat, wzc2020X WZCC20308 Shallow, round cover, WZCC2030E Shallow, round cover, WZCC2030N Shallow, round cover, WZCC2030Z Shallow, round cover, WZCC2030N Shallow, round cover, WZCC2030Z Shallow, round cover, WZCC2030N Shallow, round cover, was a second cover, which we can be a second cover, which we c WZCC20408 Shallow, square cover, WZCC2040E Shallow, square cover, WZCC2040N Shallow, square cover, WZCC2040Z Shallow, square cover, WZCC2040E Shallow, square cover, wzc. WZCC20508 Deep, round cover, WZCC2050E Deep, round cover, WZCC2050N Deep, round cover, WZCC2050Z Deep, round cover, WZCC20608 Deep, square cover, WZCC2060E Deep, square cover, WZCC2060N Deep, square cover, WZCC2060Z Deep, square cover; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available



ELECTRICAL CHARACTERISTICS	
Power consumption	max 11W
Power supply	max 300mA
Power supply unit	power supply unit not included
Control system	dimming via dimmable driver
Wiring	series
LIGHTING CHARACTERISTICS	
Number and type of LED	1 power LED High Intensity
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	4000K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	36°
Lumen output at source	960 lm (3000K, 300mA, CRI >90)
Delivered lumen output	756 lm (3000K, 300mA, 36°, CRI >90)
MECHANICAL CHARACTERISTICS	
Dimensions	ø85 mm / 85x85 mm
Weight	500 gr
Body material	body in die-cast aluminium and Bayblend, bezel and cover in die-cast aluminium
GENERAL CHARACTERISTICS	
Ingress protection	IP40, IP44 with filter
Operating temperature	0°C — +45°C
Features	UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 2x0.30 m single-core cables

PHOTOMETRIC DATA AND ACCESSORIES



PHOTOMETRIC DATA

L - 36° CRI 90 flat, round cover

		Lux max (3000K)	cd/Klm max 2915	— C0 - C180
H (m)	Ø (m)		1+1	H
1,00	0,63	2204		XX
2,00	1,26	551		
3,00	1,90	245	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
4,00	2,53	138	30°	30°
5,00	3,16	88	0°	

L - 36° CRI 90 shallow, round cover

		Lux max (3000K)	cd/Klm max 2915	—C0 - C180
H (m)	Ø (m)		1+1	H
1,00	0,63	2204		XX
2,00	1,26	551		
3,00	1,90	245	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
4,00	2,53	138	30°	30°
5,00	3,16	88	0°	50

L - 36° CRI 90 deep, round cover

		Lux max (3000K)	cd/Klm max 2583	— C0 - C180
H (m)	Ø (m)		1	XX
1,00	0,64	2343		
2,00	1,29	586		
3,00	1,93	260	\wedge	
4,00	2,58	146	30°	30°
5,00	3,22	94	0°	

L - 36° CRI 90 flat, square cover

		Lux max (3000K)	cd/Klm max 2916	— C0 - C180
H (m)	Ø (m)		1+1	XX
1,00	0,61	2204		XX
2,00	1,21	551		
3,00	1,82	245		7
4,00	2,43	138	30°	30°
5,00	3,03	88	0,	

L - 36° CRI 90 shallow, square cover

		Lux max (3000K)	cd/Klm max 2916	—C0 - C180
H (m)	Ø (m)		1+1	H
1,00	0,61	2204		XX
2,00	1,21	551		
3,00	1,82	245		
4,00	2,43	138	30°	30°
5,00	3,03	88	0°	50

L - 36° CRI 90 deep, square cover

		Lux max (3000K)	cd/Klm max 2583	—C0 - C180
H (m)	Ø (m)		1+1	XX
1,00	0,64	2343		
2,00	1,28	586	X/T	
3,00	1,92	260	\wedge	
4,00	2,55	146	30°	30°
5,00	3,19	94	0,	30

ACCESSORIES

Installation Accessories



WGCC20A1F

Round bezel for installation flush with ceiling Required installation accessories, not included





WGCC20A1T

Round bezel for rebated installation Required installation accessories, not included



PHOTOMETRIC DATA AND ACCESSORIES



WGCC20A2F

Square bezel for installation flush with ceiling Required installation accessories, not included



WZCC20108

Flat, round cover

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



Square bezel for rebated installation Required installation accessories, not included



WZCC2010E

Flat, round cover white

Required installation accessories, not included



WZCC2010N

Flat, round cover

black

Required installation accessories, not included



WZCC2010Z

Flat, round cover antique bronze

Required installation accessories, not included



WZCC20208

Flat, square cover

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



WZCC2020E

Flat, square cover

Required installation accessories, not included



WZCC2020N

Flat, square cover black

Required installation accessories, not included



WZCC2020Z

Flat, square cover antique bronze

Required installation accessories, not included

PHOTOMETRIC DATA AND ACCESSORIES





WZCC20308

Shallow, round cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC2030E

Shallow, round cover

Required installation accessories, not included



WZCC2030N

Shallow, round cover black

Required installation accessories, not included



WZCC2030Z

Shallow, round cover antique bronze

Required installation accessories, not included



WZCC20408

Shallow, square cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC2040E

Shallow, square cover white

Required installation accessories, not included



WZCC2040N

Shallow, square cover

black

Required installation accessories, not included



WZCC2040Z

Shallow, square cover

antique bronze

Required installation accessories, not included



WZCC20508

Deep, round cover primer



WZCC2050E

Deep, round cover

white

PHOTOMETRIC DATA AND ACCESSORIES



The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included

Required installation accessories, not included



WZCC2050N

Deep, round cover black

Required installation accessories, not included



WZCC20608

Deep, square cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



WZCC2050Z

Deep, round cover antique bronze Required installation accessories, not included



WZCC2060E

Deep, square cover white

Required installation accessories, not included



WZCC2060N

Deep, square cover black

Required installation accessories, not included



WZCC2060Z

Deep, square cover antique bronze

Required installation accessories, not included





WHCC20A1

Honeycomb louvre round cover: flat, shallow, deep square cover: deep





WHCC20A2

Honeycomb louvre square cover: flat, shallow

PHOTOMETRIC DATA AND ACCESSORIES





WRCC20R1D

Diffuser filter

round cover: flat, shallow, deep

square cover: deep



WRCC20S1D

Diffuser filter

square cover: flat, shallow



WRCC20R1W

Elliptical filter

Adding the filter changes the light output: please consult the photometric

data

round cover: flat, shallow, deep

square cover: deep



WRCC20S1W

Elliptical filter

Adding the filter changes the light output: please consult the photometric

data.

square cover: flat, shallow





WRCC20R1T

Transparent IP44 screen round cover: flat, shallow, deep

square cover: deep



WRCC20S1T

Transparent IP44 screen square cover: flat, shallow

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.