



Made in Italy



Combina D 3.0, code: CC3020100090L0

Recessed for indoor applications
















DESCRIPTION

recessed downlight for indoor applications; recessed (ceiling); Power consumption: max 15W; Power supply: max 400mA; Lumen output at source: 1349 lm (3000K, 400mA, CRI >90); Delivered lumen output: 1094 lm (3000K, 400mA, 36°, CRI >90); 1 power LED High Intensity, 2-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 4000K; Optics: 36°: optical system consisting of a deep-set, high-efficiency TIR lens; CRI Colour Rendering Index: >90; Body material: body made of low-copper-content die-cast aluminium alloy EN AB 46100, for excellent corrosion resistance, and flameretardant Bayblend. Trim and cover made of low-copper-content die-cast aluminium alloy EN AB 46100 for excellent resistance to corrosion; RAL finish on request; power supply unit not included; Wiring: series; includes 2x0.30 m single-core PVC cables; Control system: dimming via dimmable driver; Ingress protection; IP40, IP44 with filter; UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover; Easy to wire. The electrical cables can be attached directly to the connector, making the product easier to install; Casambi control using the Casambi app with dedicated electronics; Operating temperature: 0°C - +45°C; Appliance class: class III; Weight: 900 gr; Dimensions: ø136 mm / 136x136 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WGCC30A1F Round bezel, WGCC30A1T Round bezel, WGCC30A2F Square bezel, WGCC30A2T Square bezel, WHCC30A1 Honeycomb louvre, WRCC30R1D Diffuser filter, WRCC30R1T Transparent IP44 screen, WRCC30R1W Elliptical filter, WZCC30108 Flat, round cover, WZCC3010E Flat, round cover, WZCC3010N Flat, round cover, WZCC3010Z Flat, round cover, WZCC30208 Flat, square cover, WZCC3020E Flat, square cover, WZCC3020N Flat, square cover, WZCC3020Z Flat, square cover, WZCC30308 Shallow, round cover, WZCC3030E Shallow, round cover, WZCC3030N Shallow, round cover, WZCC3030Z Shallow, round cover, WZCC30408 Shallow, square cover, WZCC3040E Shallow, square cover, WZCC3040N Shallow, square cover, WZCC3040Z Shallow, square cover, WZCC30508 Deep, round cover, WZCC3050E Deep, round cover, WZCC3050N Deep, round cover, WZCC3050Z Deep, round cover, WZCC30608 Deep, square cover, WZCC3060E Deep, square cover, WZCC3060N Deep, square cover, WZCC3060Z Deep, square cover; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available



Power consumption	max 15W
Power supply	max 400mA
Power supply unit	power supply unit not included
Control system	dimming via dimmable driver
Viring	series
LIGHTING CHARACTERISTICS	
Number and type of LED	1 power LED High Intensity
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	4000K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	36°
umen output at source	1349 lm (3000K, 400mA, CRI >90)
Delivered lumen output	1094 lm (3000K, 400mA, 36°, CRI >90)
MECHANICAL CHARACTERISTICS	
Dimensions	ø136 mm / 136x136 mm
Veight	900 gr
Body material	body in die-cast aluminium and Bayblend, bezel and cover in die-cast aluminium
GENERAL CHARACTERISTICS	
ngress protection	IP40, IP44 with filter
Operating temperature	0°C — +45°C
Features Features	UGR <13 for versions with flat and shallow covers, UGR <19 for versions with deep cover
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Appliance class	class III
Valkover	no
Orive-over	no
Power cables	includes 2x0.30 m single-core PVC cables
Notes	Easy to wire. The electrical cables can be attached directly to the

PHOTOMETRIC DATA AND ACCESSORIES



PHOTOMETRIC DATA

L - 36° CRI 90 flat, round cover

		Lux max (3000K)	cd/Klm max 2538	—C0 - C180
H (m)	Ø (m)		1	H
1,00	0,65	2776		XX
2,00	1,30	694		
3,00	1,95	308	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
4,00	2,60	174	30°	30°
5,00	3,25	111	0°	

L - 36° CRI 90 shallow, round cover

		Lux max (3000K)	cd/Klm max 2538	C0 - C180
H (m)	Ø (m)		1	H
1,00	0,65	2776		XX
2,00	1,30	694		
3,00	1,95	308	\wedge	
4,00	2,60	174	30°	30°
5,00	3,25	111	0°	

L - 36° CRI 90 deep, round cover

		Lux max (3000K)	cd/Klm max 2374	— C0 - C180
H (m)	Ø (m)		1	H
1,00	0,65	2797		
2,00	1,30	699		
3,00	1,95	311		
4,00	2,60	175	30°	30°
5,00	3,24	112	0°	

L - 36° CRI 90 flat, square cover

		Lux max (3000K)	cd/Klm max 2538	— C0 - C180
H (m)	Ø (m)		1+1/	XX
1,00	0,64	2776		XX
2,00	1,28	694		
3,00	1,92	308	\wedge	
4,00	2,57	174	30°	30°
5,00	3,21	111	0'	

L - 36° CRI 90 shallow, square cover

		Lux max (3000K)	cd/Klm max 2538	—C0 - C180
H (m)	Ø (m)		1+1	H
1,00	0,64	2776		XX
2,00	1,28	694		
3,00	1,92	308		
4,00	2,57	174	30°	30°
5,00	3,21	111	0°	30

L - 36° CRI 90 deep, square cover

		Lux max (3000K)	cd/Klm max 2374	—C0 - C180
H (m)	Ø (m)		1+1	XX
1,00	0,64	2795		
2,00	1,28	699		
3,00	1,92	311		
4,00	2,56	175	30°	30°
5,00	3,20	112	0°	50

ACCESSORIES

Installation Accessories



WGCC30A1F

Round bezel for installation flush with ceiling Required installation accessories, not included





WGCC30A1T

Round bezel for rebated installation Required installation accessories, not included



PHOTOMETRIC DATA AND ACCESSORIES



WGCC30A2F

Square bezel for installation flush with ceiling Required installation accessories, not included



WZCC30108

Flat, round cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



Square bezel for rebated installation Required installation accessories, not included



WZCC3010E

Flat, round cover white

Required installation accessories, not included



WZCC3010N

Flat, round cover

black

Required installation accessories, not included



WZCC3010Z

Flat, round cover antique bronze

Required installation accessories, not included



WZCC30208

Flat, square cover

prime

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



WZCC3020E

Flat, square cover

white

Required installation accessories, not included



WZCC3020N

Flat, square cover

black

Required installation accessories, not included



WZCC3020Z

Flat, square cover antique bronze

Required installation accessories, not included

PHOTOMETRIC DATA AND ACCESSORIES





WZCC30308

Shallow, round cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC3030E

Shallow, round cover

Required installation accessories, not included



WZCC3030N

Shallow, round cover black Required installation accessories, not included



WZCC3030Z

Shallow, round cover antique bronze Required installation accessories, not included



WZCC30408

Shallow, square cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e: two-pack polyurethane varnishes, two-pack acrylic paints Required installation accessories, not included



WZCC3040E

Shallow, square cover white

Required installation accessories, not included



WZCC3040N

Shallow, square cover black

Required installation accessories, not included



WZCC3040Z

Shallow, square cover antique bronze Required installation accessories, not included



WZCC30508

Deep, round cover primer



WZCC3050E

Deep, round cover white

PHOTOMETRIC DATA AND ACCESSORIES



The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included

Required installation accessories, not included



WZCC3050N

Deep, round cover black

Required installation accessories, not included



WZCC30608

Deep, square cover primer

The paints that can be used on primed lighting fixtures are the same ones that are suitable for use on masonry surfaces, i.e. two-pack polyurethane varnishes, two-pack acrylic paints
Required installation accessories, not included



WZCC3050Z

Deep, round cover antique bronze Required installation accessories, not included



WZCC3060E

Deep, square cover white

Required installation accessories, not included



WZCC3060N

Deep, square cover black

Required installation accessories, not included



WZCC3060Z

Deep, square cover antique bronze

Required installation accessories, not included






WHCC30A1

Honeycomb louvre

round and square covers: flat, shallow







DATASHEET

COMBINA D 3.0, CODE: CC3020100090L0

PHOTOMETRIC DATA AND ACCESSORIES



WRCC30R1D

Diffuser filter

round and square covers: flat, shallow

WRCC30R1W

Elliptical filter

Adding the filter changes the light output: please consult the photometric data

round and square covers: flat, shallow

Other



WRCC30R1T

Transparent IP44 screen round and square covers: flat, shallow

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.