



Made in Italy

Pivot 2.0, code: CP200110005R3T

Projectors for outdoor applications







#### **DESCRIPTION**

projector for outdoor applications; surface mounted (ceiling, wall, ground, spike), surface mounted (ceiling, wall, floor); Power consumption: 14W; Power supply: 24Vdc; Lumen output at source: 1173 lm (3000K, 14W, CRI >90); Delivered lumen output: 862 lm (3000K, 25°, 14W, CRI >90); 1 COB LED, 3-step MacAdam, 50 000h L95 B10 (Ta 25°C); LED colour: 3000K; Optics: optical range 15°-43°: optical system consisting of a high-efficiency TIR lens combined with a magnet-adjusted rotary zoom controller for extreme flexibility of choice of light emission; CRI Colour Rendering Index: >90; Body material: body made of ANTICORODAL EN AW 6082 low-copper-content aluminium alloy for excellent resistance to corrosion, made entirely on a CNC lathe; Finishes: cor-ten finish obtained through an initial treatment with a ceramic nanoparticle coating, to prepare for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1000 hours of salt spray.: RAL finish on request: Screen material: 3-mm-thick transparent extra-clear glass with vitrified serigraphy, high transmittance to ensure chromatic uniformity of light and tempered for excellent resistance to knocks and scratches; Seals: The NBR nitrile rubber O-rings ensure the fixture's IP rating is preserved, guaranteeing continued protection; power supply unit not included; includes 1.50 m neoprene cable, H05RN-F 2x0,35/0,75 Ø6,3 mm; Ingress protection: IP66; Impact resistance: IK08; manual zoom lens adjustable using magnet included 13°x68° optics adjustable through 360° using magnet included; Casambi control using the Casambi app with dedicated electronics; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; Operating temperature: -20°C - +45°C; Glow wire test: 960°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class III; Weight: 640 g; Dimensions: Ø60x96 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WB1001T Standard snoot - cor-ten, WB1002T Asymmetrical snoot - cor-ten, WB1003N Barn doors - black, WE0201 Magnet for adjustable optics and zoom lens, WP0100 Spike for in-ground installation; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

04/11/2025 Rev. 10/2024

# DATASHEET TECHNICAL DATA



Power consumption	14W
·	24Vdc
Power supply	
Power supply unit	power supply unit not included
LIGHTING CHARACTERISTICS	
Number and type of LED	1 COB LED
Average LED life	50 000h L95 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	>90
Binning	3-step MacAdam
Optics	optical range 15°-43°
Lumen output at source	1173 lm (3000K, 14W, CRI >90)
Delivered lumen output	862 lm (3000K, 25°, 14W, CRI >90)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø60x96 mm
Weight	640 g
Finishes	cor-ten
Mounting	with screws and plugs
Body material	body in anticorodal aluminium
Screen material	screen in serigraphed, transparent, tempered extra-clear glass
GENERAL CHARACTERISTICS	
Ingress protection	IP66
Operating temperature	-20°C — +45°C
Impact resistance	IK08
Features	manual zoom lens adjustable using magnet included 13°x68° optics adjustable through 360° using magnet included
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 1.50 m neoprene cable, H05RN-F 2x0,35/0,75 Ø6,3 mm
Protection systems	IPS (Intelligent Protection System)
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006
Notes	Casambi control using the Casambi app with dedicated electronics


#### PIVOT 2.0, CODE: CP200110005R3T

# PHOTOMETRIC DATA AND ACCESSORIES



#### PHOTOMETRIC DATA

R3 - zoom 15° (15°-43°) CRI80



#### R3 - zoom 43° (15°-43°) CRI80

		Lux ma	x (3000K)	cd/Klm max 1731	— C0 - C180
H (m)	Ø (m)	10W	14W	1	H
1.00	0.78	1089	1387		XX
2.00	1.56	272	347		
3.00	2.35	121	154		
4.00	3.13	68	87	30°	30°
5.00	3.91	44	55	0°	

## **ACCESSORIES**

## Installation Accessories





WP0100 Spike for in-ground installation

## Anti-glare



WB1001T Standard snoot - cor-ten



WB1002T Asymmetrical snoot - cor-ten



WB1003N Barn doors - black

## Other



WE0201

# DATASHEET PIVOT 2.0, CODE: CP200110005R3T PHOTOMETRIC DATA AND ACCESSORIES



Magnet for ac	diustable d	optics	and	zoom	lens

 $L\&L\ Luce\&Light\ SRL\ reserves\ the\ right\ to\ change\ the\ information\ contained\ in\ this\ document\ at\ any\ time\ without\ prior\ notice\ being\ given.$