Made in Italy


10/11/2026 Rev. 06/2024

Brom 4.0, code: BR400625SSI

Wall mounted for outdoor applications

kg 0,80 IP66 IK08





DESCRIPTION

wall mounted for outdoor applications, double beam; surface mounted (wall); Power consumption: max 12W; Power supply: max 500mA; Lumen output at source: 872 lm (3000K, 500mA); Delivered lumen output: 502 lm (3000K, 500mA, 20°); 6 power LEDs, 1/4 ANSI BIN, 50 000h L90 B10 (Ta 25°C); LED colour: 3000K; UP optics: 12°; DOWN optics: 12°; CRI Colour Rendering Index: 80; Body material: body and trim in AISI 316L stainless steel; RAL finish on request; Screen material: screen in tempered, transparent extra-clear glass; power supply unit not included; Wiring: series; includes 2x0.30 m single-core cables; Control system: dimming via dimmable driver; Ingress protection: IP66; Impact resistance: IK08; Operating temperature: -20°C — +45°C; Glow wire test: 960°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class III; Weight: 800 g; Dimensions: 70x70x150 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption


Status: Product being discontinued

ELECTRICAL CHARACTERISTICS	
Power consumption	max 12W
Power supply	max 500mA
Power supply unit	power supply unit not included
Control system	dimming via dimmable driver
Wiring	series
LIGHTING CHARACTERISTICS	
Number and type of LED	6 power LEDs
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	80
Binning	1/4 ANSI BIN
UP optics	12°
DOWN optics	12°
Lumen output at source	872 lm (3000K, 500mA)
Delivered lumen output	502 lm (3000K, 500mA, 20°)
MECHANICAL CHARACTERISTICS	
Dimensions	70x70x150 mm
Weight	800 g
Mounting	with screws and plugs
Body material	body and trim in AISI 316L stainless steel
Screen material	screen in transparent, tempered extra-clear glass
GENERAL CHARACTERISTICS	
Ingress protection	IP66
Operating temperature	-20°C — +45°C
Impact resistance	IK08
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 2x0.30 m single-core cables
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006

PHOTOMETRIC DATA

S - 12°

H (m)	∅ (m)	Lux max (3000K) 6W	cd/Klm max 13637
0.50	0.11	15164	
1.00	0.22	3791	
1.50	0.34	1685	
2.00	0.45	948	
2.50	0.56	607	
3.00	0.67	421	





Double beam

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.