
Made in Italy

Metope 2.2, code: TM220010015SSH

Wall mounted for outdoor applications

24Vdc kg 0,68 IP65 IK05





DESCRIPTION

wall mounted for outdoor applications, double beam; surface mounted (wall); Power consumption: 13W; Power supply: 24Vdc; Lumen output at source: 1590 lm; Delivered lumen output: 1002 lm (52°, 3000K); 2 COB LEDs, 2-step MacAdam, 60 000h L80 B10 (Ta 25°C); LED colour: 3000K; Optics: 21°+21°: double-beam optical system consisting of a high-efficiency, recessed TIR lens combined with a high-quality technical filter; CRI Colour Rendering Index: >90; Body material: body made of low-copper-content die-cast aluminium alloy EN AB 47100 for excellent resistance to corrosion; Finishes: anthracite finish obtained through an initial treatment with a ceramic nanoparticle coating, to prepare for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1500 hours of salt spray. Paints compliant with the Qualicoat standard used in the automotive sector; RAL finish on request; Screen material: 3-mm-thick transparent extra-clear glass, with high transmittance to ensure chromatic uniformity of light and tempered for excellent resistance to knocks and scratches, with RAL 7015 grey vitrified serigraphy around the edge; Installation: the symmetrical mounting bracket means the device can be installed without any restrictions on orientation between the bracket and the body of the device; power supply unit not included; Control system: ON/OFF, Casambi; Ingress protection: IP65; Impact resistance: IK05; Non-standard light output combinations available on request; spacer with RAL finish available on request; only compatible with Casambi in the 24Vdc version; Operating temperature: -20°C — +50°C; Glow wire test: 960°C; Appliance class: class III; Weight: 680 g; Dimensions: 51x76x150 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: honeycomb louvre, WDA20H Spacer H 15 mm - anthracite; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption


Status: Available

ELECTRICAL CHARACTERISTICS	
Power consumption	13W
Power supply	24Vdc
Power supply unit	power supply unit not included
Control system	ON/OFF, Casambi
LIGHTING CHARACTERISTICS	
Number and type of LED	2 COB LEDs
Average LED life	60 000h L80 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	21°+21°
Lumen output at source	1590 lm
Delivered lumen output	1002 lm (52°, 3000K)
MECHANICAL CHARACTERISTICS	
Dimensions	51x76x150 mm
Weight	680 g
Finishes	anthracite
Mounting	with screws and plugs
Body material	body in die-cast aluminium
Screen material	screen in serigraphed-grey and transparent, tempered extra-clear glass
GENERAL CHARACTERISTICS	
Ingress protection	IP65
Operating temperature	-20°C — +50°C
Impact resistance	IK05
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Notes	Non-standard light output combinations available on request; spacer with RAL finish available on request; only compatible with Casambi in the 24Vdc version

PHOTOMETRIC DATA


SS – 21°

H (m)	∅ (m)	Lux max (3000K)	cd/Klm max 4909 — C0 - C180
1.00	0.37	2288	
2.00	0.74	572	
3.00	1.11	254	
4.00	1.48	143	
5.00	1.85	92	




ACCESSORIES

Installation Accessories



WDA20H
Spacer H 15 mm - anthracite

Anti-glare



honeycomb louvre

built into the lighting fixture
Can be fitted on all optics except for diffuse optics
Add the optical accessory in the code generator

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.