


Made in Italy

 **Reiko 3.0, code: RK3001000050X5**  
Projectors for outdoor applications







 kg 1,250
 





## DESCRIPTION

projector for outdoor applications; surface mounted (ceiling, wall, ground, spike); Power consumption: 15W; Power supply: 24Vdc; Lumen output at source: 1747 lm (3000K, 15W, CRI 80); Delivered lumen output: 1124 lm (3000K, 37°, 15W, CRI 80); 1 COB LED, 2-step MacAdam, 60 000h L90 B10 (Ta 25°C); LED colour: 3000K; Optics: adjustable 27°x64°: optical system consisting of a high-efficiency TIR lens combined with a high-quality elliptical technical filter and integrated with magnetic material for adjusting the ellipsis (patent pending); CRI Colour Rendering Index: 80; Body material: body made of low-copper-content die-cast aluminium alloy EN AB 47100 for excellent resistance to corrosion. Bracket in AISI 316L stainless steel, tumble finished and painted; Finishes: jasper green finish obtained through an initial treatment with a ceramic nanoparticle coating, to prepare for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1500 hours of salt spray. Paints compliant with the Qualicoat standard used in the automotive sector; RAL finish on request; Screen material: 4-mm-thick transparent extra-clear glass, with high transmittance to ensure chromatic uniformity of light and tempered for excellent resistance to knocks and scratches, with RAL 7015 grey vitrified serigraphy around the edge; power supply unit not included; includes 1.50 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm; Ingress protection: IP66, IP69 (80°C); Impact resistance: IK06; Casambi control using the Casambi app with dedicated electronics; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; Operating temperature: -20°C — +45°C; Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 1250 g; Dimensions: 85x85x90 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WBA125 Standard square snoot - jasper green, WBA135 Asymmetrical square snoot - jasper green, WE0201 Magnet for adjustable optics and zoom lens, WP0300 Spike for in-ground installation, WP1004 Fastener strap - 5 m, WP10065 Spike for in-ground installation - h 500 mm - jasper green, WP10075 Spike for in-ground installation - h 800 mm - jasper green; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

### ELECTRICAL CHARACTERISTICS

Power consumption	15W
Power supply	24Vdc
Power supply unit	power supply unit not included

### LIGHTING CHARACTERISTICS

Number and type of LED	1 COB LED
Average LED life	60 000h L90 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	80
Binning	2-step MacAdam
Optics	adjustable 27°x64°
Lumen output at source	1747 lm (3000K, 15W, CRI 80)
Delivered lumen output	1124 lm (3000K, 37°, 15W, CRI 80)

### MECHANICAL CHARACTERISTICS

Dimensions	85x85x90 mm
Weight	1250 g
Finishes	jasper green
Body material	body in die-cast aluminium, AISI 316L stainless steel bracket
Screen material	screen in serigraphed-grey and transparent, tempered extra-clear glass



### GENERAL CHARACTERISTICS

Ingress protection	IP66, IP69 (80°C)
Operating temperature	-20°C — +45°C
Impact resistance	IK06
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 1.50 m neoprene cable H05RN-F 2x0.75/0.75 Ø6.3 mm
Protection systems	IPS (Intelligent Protection System)
Photobiological safety	in accordance with IEC TR 62778:2014
Notes	Casambi control using the Casambi app with dedicated electronics

PHOTOMETRIC DATA

X – 27°x64° Orientabile CRI80


H (m)	Ø (m)	Ø (m)	15W	Lux max (3000K)	cd/Klm max 1635
2.00	0.95	2.52	221		
4.00	1.90	5.03	55		
6.00	2.85	7.55	25		
8.00	3.80	10.07	14		
10.00	4.75	12.58	9		




27°x64°

ACCESSORIES


Installation Accessories



WP0300  
Spike for in-ground installation




WP10065  
Spike for in-ground installation - h 500 mm - jasper green




WP10075  
Spike for in-ground installation - h 800 mm - jasper green

Anti-glare



WBA125  
Standard square snoot - jasper green



WBA135  
Asymmetrical square snoot - jasper green

Other



**WE0201**

Magnet for adjustable optics and zoom lens



**WP1004**

Fastener strap - 5 m

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.