







Made in Italy


 Trevi 2.1, code: TR2100000090WP  
Linear profiles for outdoor and underwater applications

25/05/2026 Rev. 02/2024


 kg 3.10
 






## DESCRIPTION

linear profile for outdoor and underwater applications; surface mounted (ceiling, wall, ground), max depth 10 m; Power consumption: 42W; Power supply: 24Vdc; Lumen output at source: 5712 lm (3000K); Delivered lumen output: 4484 lm (3000K, 38°x94°); 112 mid-power LEDs, 3-step MacAdam, 60 000h L80 B10 (Ta 25°C); LED colour: 4000K; Optics: 38°x94°: optical system composed of a series of equidistant light sources, 10 mm apart, and of a high-efficiency PMMA linear lens made by an extrusion process; CRI Colour Rendering Index: 80; Body material: end caps in AISI 316L stainless steel. Heat sink made of Anticorodal® low-copper-content aluminium EN AW 6060 T5 for excellent heat dissipation, manufactured from an extruded profile; Screen material: screen in bi-material anti-UV polycarbonate (transparent at the top and grey below), with high transmittance to ensure colour uniformity; power supply unit not included; includes 5 m neoprene cable, H05RN-F 2x1,00 Ø6.3 mm; Ingress protection: IP65, IP68; Impact resistance: IK10; Casambi control using the Casambi app with dedicated electronics; Operating temperature: -20°C — +45°C (installation outdoors), 0°C — +45°C (installation underwater); Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 3100 g; Dimensions: Ø50x1213 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WMA04 Clips pair, WMA05 Pair of tamper-resistant clips, WMA07 Suspension kit; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

### ELECTRICAL CHARACTERISTICS

Power consumption	42W
Power supply	24Vdc
Power supply unit	power supply unit not included

### LIGHTING CHARACTERISTICS

Number and type of LED	112 mid-power LEDs
Average LED life	60 000h L80 B10 (Ta 25°C)
LED colour	4000K
CRI Colour Rendering Index	80
Binning	3-step MacAdam
Optics	38°x94°
Lumen output at source	5712 lm (3000K)
Delivered lumen output	4484 lm (3000K, 38°x94°)

### MECHANICAL CHARACTERISTICS


Dimensions	Ø50x1213 mm
Weight	3100 g
Mounting	with clips, screws and plugs
Body material	end caps in AISI 316L stainless steel, internal anticorrosion aluminium heat sink
Screen material	screen in transparent polycarbonate

### GENERAL CHARACTERISTICS

Ingress protection	IP65, IP68
Operating temperature	-20°C — +45°C (installation outdoors), 0°C — +45°C (installation underwater)
Impact resistance	IK10
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 5 m neoprene cable, H05RN-F 2x1,00 Ø6.3 mm
Photobiological safety	in accordance with IEC TR 62778:2014
Notes	Casambi control using the Casambi app with dedicated electronics

PHOTOMETRIC DATA


W – 38°x94°



38°x94°

ACCESSORIES


Other



WMA04

Clips pair

Required installation accessories, not included



WMA05

Pair of tamper-resistant clips

Required installation accessories, not included



WMA07

Suspension kit

Required installation accessories, not included

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.