
Made in Italy


12/11/2026 Rev. 02/2024

Trevi 2.1, code: TR2100000090WP

Linear profiles for outdoor and underwater applications

kg 3,10 IP65 IP68 IK10





DESCRIPTION

linear profile for outdoor and underwater applications; surface mounted (ceiling, wall, ground), max depth 10 m; Power consumption: 42W; Power supply: 24Vdc; Lumen output at source: 5712 lm (3000K); Delivered lumen output: 4484 lm (3000K, 38°x94°); 112 mid-power LEDs, 3-step MacAdam, 60 000h L80 B10 (Ta 25°C); LED colour: 4000K; Optics: 38°x94°: optical system composed of a series of equidistant light sources, 10 mm apart, and of a high-efficiency PMMA linear lens made by an extrusion process; CRI Colour Rendering Index: 80; Body material: end caps in AISI 316L stainless steel. Heat sink made of Anticorodal® low-copper-content aluminium EN AW 6060 T5 for excellent heat dissipation, manufactured from an extruded profile; Screen material: screen in bi-material anti-UV polycarbonate (transparent at the top and grey below), with high transmittance to ensure colour uniformity; power supply unit not included; includes 5 m neoprene cable, H05RN-F 2x1,00 Ø6.3 mm; Ingress protection: IP65, IP68; Impact resistance: IK10; Casambi control using the Casambi app with dedicated electronics; Operating temperature: -20°C — +45°C (installation outdoors), 0°C — +45°C (installation underwater); Glow wire test: 960°C; Photobiological safety: in accordance with IEC TR 62778:2014; Appliance class: class III; Weight: 3100 g; Dimensions: Ø50x1213 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WMA04 Clips pair, WMA05 Pair of tamper-resistant clips, WMA07 Suspension kit; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption


Status: Available

ELECTRICAL CHARACTERISTICS	
Power consumption	42W
Power supply	24Vdc
Power supply unit	power supply unit not included
LIGHTING CHARACTERISTICS	
Number and type of LED	112 mid-power LEDs
Average LED life	60 000h L80 B10 (Ta 25°C)
LED colour	4000K
CRI Colour Rendering Index	80
Binning	3-step MacAdam
Optics	38°x94°
Lumen output at source	5712 lm (3000K)
Delivered lumen output	4484 lm (3000K, 38°x94°)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø50x1213 mm
Weight	3100 g
Mounting	with clips, screws and plugs
Body material	end caps in AISI 316L stainless steel, internal anticorodal aluminium heat sink
Screen material	screen in transparent polycarbonate
GENERAL CHARACTERISTICS	
Ingress protection	IP65, IP68
Operating temperature	-20°C — +45°C (installation outdoors), 0°C — +45°C (installation underwater)
Impact resistance	IK10
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 5 m neoprene cable, H05RN-F 2x1,00 Ø6.3 mm
Photobiological safety	in accordance with IEC TR 62778:2014
Notes	Casambi control using the Casambi app with dedicated electronics

PHOTOMETRIC DATA

W – 38°x94°

H (m)	Ø (m)	Ø (m)	Lux max (3000K) 42W
1.00	0.68	2.15	2995
2.00	1.37	4.31	749
3.00	2.05	6.46	333
4.00	2.74	8.62	187
5.00	3.42	10.77	120







38°x94°

ACCESSORIES

Other



WMA04
Clips pair
Required installation accessories, not included



WMA05
Pair of tamper-resistant clips
Required installation accessories, not included



WMA07
Suspension kit
Required installation accessories, not included

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.