




Made in Italy

 **Krill 4.4, code: KI442010005R3N**  
Projectors for indoor applications

09/05/2026 Rev. 02/2024



## DESCRIPTION

projector for indoor applications; surface mounted (shop windows, display cabinets, shelves, ceiling, wall); Power consumption: max 9W; Power supply: max 250mA; Lumen output at source: 893 lm; Delivered lumen output: 649 lm (3000K, 17°); 1 COB LED, 2-step MacAdam, 60 000h L90 B10 (Ta 25°C); LED colour: 3000K; Optics: optical range 17°—39°; CRI Colour Rendering Index: >90; Body material: body made of ANTICORODAL EN AW 6026 low-copper-content aluminium alloy for excellent resistance to corrosion, made entirely on a CNC lathe. Joint made of brass and produced entirely on a CNC lathe.; Finishes: Cylindrical cover and joint painted black, radiator electro-coloured black (RAL 9005); RAL finish on request; Installation: versatile installation thanks to its accessories: arm with fixing base, nipple coupler, magnetic plate, fixing springs and ceiling rose; power supply unit not included; Wiring: series; includes 1.50 m PVC cable FROR 2x0.35 Ø3.5 mm; Control system: ON/OFF; Ingress protection: IP40; Casambi control using the Casambi app with dedicated electronics; Operating temperature: 0°C — +45°C; Glow wire test: 960°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class III; Weight: 300 g; Dimensions: ø45x94 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WDA06N Fixing base, WDA07N Magnetic plate, WDA08N Rigid arm - h 150 mm, WDA09N Rigid arm - h 300 mm, WDA10N Ceiling rose, WE0201 Magnet for adjustable optics and zoom lens, WF0110 PVC cable FROR 2x0,35 Ø3,5 mm, WGA01 Nipple coupler, WGA09N Retaining spring clip Ø45mm; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

**ELECTRICAL CHARACTERISTICS**

Power consumption	max 9W
Power supply	max 250mA
Power supply unit	power supply unit not included
Control system	ON/OFF
Wiring	series

**LIGHTING CHARACTERISTICS**

Number and type of LED	1 COB LED
Average LED life	60 000h L90 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	>90
Binning	2-step MacAdam
Optics	optical range 17° – 39°
Lumen output at source	893 lm
Delivered lumen output	649 lm (3000K, 17°)

**MECHANICAL CHARACTERISTICS**


Dimensions	ø45x94 mm
Weight	300 g
Finishes	black RAL 9005
Body material	body in anticorodal aluminium, joint in brass

**GENERAL CHARACTERISTICS**


Ingress protection	IP40
Operating temperature	0°C – +45°C
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°C
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 1.50 m PVC cable FROR 2x0.35 Ø3.5 m
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006
Notes	Casambi control using the Casambi app with dedicated electronics

PHOTOMETRIC DATA

R3 – zoom L 17°




R3 – zoom L 39°



ACCESSORIES

Installation Accessories




**WDA06N**  
Fixing base  
black

Required installation accessories, not included




**WDA08N**  
Rigid arm - h 150 mm  
black

Order together with the fixing base or the nipple




**WDA07N**  
Magnetic plate  
black

Required installation accessories, not included



**WDA09N**  
Rigid arm - h 300 mm  
black

Order together with the fixing base or the nipple



**WDA10N**  
Ceiling rose  
black

Required installation accessories, not included



**WGA09N**  
Retaining spring clip Ø45mm  
black

Required installation accessories, not included

Other




**WF0110**  
PVC cable FROR 2x0,35 Ø3,5 mm  
your choice of length

To be ordered by meter for lengths other than the standard one (1.5 m)

**WE0201**

Magnet for adjustable optics and zoom lens

**WGA01**

Nipple coupler

Required installation accessories, not included

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.