




Made in Italy



04/11/2025 Rev. 09/2024
























#### **DESCRIPTION**

projector for outdoor applications; surface mounted (ceiling, wall, floor); Power consumption: 37W; Power supply: 230Vac; Lumen output at source: 3402 lm (3000K, CRI 80); Delivered lumen output: 2205 lm (3000K, 66°x11° adjustable, CRI 80); 4 high-intensity power LEDs, 3-step MacAdam, 50 000h L90 B10 (Ta 25°C); LED colour: 3000K; Optics: adjustable 66°x11°: optical system consisting of a high-efficiency TIR lens combined with a highquality elliptical technical filter and integrated with magnetic material for adjusting the ellipsis (patented); CRI Colour Rendering Index: 80; Body material: body made of die-cast aluminium. Trim in AISI 316L stainless steel, made with a CNC lathe then micro-peened, passivated and electropolished to guarantee excellent corrosion resistance. Bracket in AISI 316L stainless steel, tumble finished and painted; Finishes: die-cast body painted anthracite with an initial treatment of a ceramic nanoparticle coating, as surface preparation for painting, followed by a coat of epoxy paint and one of polyester paint to provide corrosion resistance of more than 1500 hours of salt spray. Paints compliant with the Qualicoat standard (automotive standard); Screen material: 15-mm-thick tempered, transparent extra-clear glass, with vitrified serigraphy, to ensure chromatic uniformity of light and excellent resistance to knocks and scratches; built-in power supply unit; includes 1.5 m neoprene cable H05RN-F 3x1,0 Ø7 mm; Control system: ON/OFF; Ingress protection: IP66; Impact resistance: IK10; 66°x11° optics adjustable through 360° using the magnet provided; DALI version available on request; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit: The PID (Protective Impedance Device) protects lighting fixtures from electrical phenomena external to the system, such as static electricity accumulation or electromagnetic interference coming from the mains power. Generally, these are events with a low energy content; The SPD (Surge Protection Device) protects lighting fixtures from electrical phenomena external to the system, such as power surges. In particular, this device is specifically for protection against serious events with a high energy content; Operating temperature: -20°C - +45°C; Glow wire test: 960°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class I; Weight: 6000 g; Dimensions: Ø252x138 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WE0201 Magnet for adjustable optics and zoom lens, WN7100 Antifall kit; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

# DATASHEET TECHNICAL DATA



Power consumption	37W	
Power supply	230Vac	
Power supply unit	built-in power supply unit	
Control system	ON/OFF	
LIGHTING CHARACTERISTICS		
Number and type of LED	4 high-intensity power LEDs	
Average LED life	50 000h L90 B10 (Ta 25°C)	
LED colour	3000K	
CRI Colour Rendering Index	80	
Binning	3-step MacAdam	
Optics	adjustable 66°x11°	
umen output at source	3402 lm (3000K, CRI 80)	
Delivered lumen output	2205 lm (3000K, 66°x11° adjustable, CRI 80)	
MECHANICAL CHARACTERISTICS		
Dimensions	Ø252x138 mm	
Veight	6000 g	
Finishes	anthracite	
Mounting	with screws and plugs	
Body material	body in die-cast aluminium, trim in AISI 316L stainless steel	
Screen material	screen in serigraphed, transparent, tempered extra-clear glass	
GENERAL CHARACTERISTICS		
ngress protection	IP66	
Operating temperature	-20°C — +45°C	
mpact resistance	IK10	
Features	66°x11° optics adjustable through 360° using the magnet provided	
Energy efficiency class	F (light source) in accordance with EU 2019/2015	
Glow wire test	960°C	
Appliance class	class I	
Valkover	no	
National Association	no	
Orive-over	includes 1.5 m neoprene cable H05RN-F 3x1,0 Ø7 mm	
Prive-over Power cables	includes 1.5 in neopiene cable hoshin-i 3x1,0 97 iniin	
	IPS (Intelligent Protection System); PID (Protective Impedance Device); SPD (Surge Protection Device)	



## PHOTOMETRIC DATA



		Lux max (3000K )	cd/Klm max 4449	— C0 - C180 — C90 - C270
H (m) Ø	i (m) Ø (m)	37W		H
2.00	2.59 0.40	2453		XX
4.00	5.19 0.80	613		
6.00	7.78 1.19	273	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
8.00 1	0.38 1.59	153	30°	30°
10.00 1	2.97 1.99	98	0°	



## **ACCESSORIES**

#### Other



WE0201
Magnet for adjustable optics and zoom lens



WN7100 Anti-fall kit

 $L\&L\ Luce\&Light\ SRL\ reserves\ the\ right\ to\ change\ the\ information\ contained\ in\ this\ document\ at\ any\ time\ without\ prior\ notice\ being\ given.$