


Made in Italy



Moby 1.1, code: MY1100YSV  
Recessed for underwater applications

24/04/2024 Rev. 31



## DESCRIPTION

recessed for underwater applications (suitable for use in seawater, only suitable for underwater applications); recessed (wall), max depth 10 m; Power consumption: 9W; Power supply: 24Vdc; Lumen output at source: 260 lm; Delivered lumen output: 184 lm (34°); 1 cyan power LED group, 50 000h L90 B10 (Ta 25°C); LED colour: shades of cyan; Optics: 22°: optical system consisting of a high-efficiency, deep-set TIR lens combined with a high-quality technical filter; Body material: body made of heat-dissipating technopolymer with a thermal conductivity equal to that of stainless steel; Screen material: glass cover in 12-mm-thick, tempered extra-clear glass with vitrified serigraphy suitable for installations in seawater and guaranteeing resistance to corrosion and to knocks and scratches. Mixing chamber to ensure the light's chromatic uniformity.; power supply unit not included; includes 5 m FEP+RUB cable (equivalent to H05RN-F cable), 6x0,50 Ø6.3 mm; Ingress protection: IP65, IP68; Impact resistance: IK10; not suitable for use in swimming pools with liners; Casambi control using the Casambi app with dedicated electronics; Protection systems: IPS (Intelligent Protection System) protects lighting fixtures from water infiltrations, which can occur if there are faulty junctions between the cables in outdoor or underwater applications. This innovation, patented by L&L, also guarantees electrical protection against polarity reversal, hot plugging, ESD and power surges, which can occur if there are faults in the electrical circuit; This is an NTC thermistor mounted on the LED board to protect the lighting fixture against overheating. Should the product function at an operating temperature greater than the maximum temperature at which it can operate correctly, the protection is activated and gradually reduces the power. The NTC causes the integrated electronic parts to cool down to avoid the lighting fixture instantly switching itself off. When the operating temperature is again within normal range, the NTC automatically restores the lighting fixture's original operating conditions; Operating temperature: 0°C — +45°C (installation underwater); Glow wire test: 960°; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class III; Weight: 1420 g; Dimensions: Ø180x134 mm; Cutout dimensions: Ø200 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; Accessories: WC5201 Outer casing, WH0401 Honeycomb louvre ; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption

Status: Available

### ELECTRICAL CHARACTERISTICS

Power consumption	9W
Power supply	24Vdc
Power supply unit	power supply unit not included

### LIGHTING CHARACTERISTICS

Number and type of LED	1 cyan power LED group
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	shades of cyan
Optics	22°
Lumen output at source	260 lm
Delivered lumen output	184 lm (34°)

### MECHANICAL CHARACTERISTICS


Dimensions	Ø180x134 mm
Weight	1420 g
Mounting	with outer casing
Body material	body in thermally conductive technopolymer
Screen material	glass cover with vitrified serigraphy
Cutout dimensions	Ø200 mm

### GENERAL CHARACTERISTICS

Ingress protection	IP65, IP68
Operating temperature	0°C — +45°C (installation underwater)
Impact resistance	IK10
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Glow wire test	960°
Appliance class	class III
Walkover	no
Drive-over	no
Power cables	includes 5 m FEP+RUB cable (equivalent to H05RN-F cable), 6x0,50 Ø6.3 mm
Protection systems	IPS (Intelligent Protection System); NTC (thermistor mounted on LED board)
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006
Notes	not suitable for use in swimming pools with liners; Casambi control using the Casambi app with dedicated electronics

## PHOTOMETRIC DATA

S - 22°




## ACCESSORIES

### Installation Accessories



**WC5201**  
 Outer casing

### Anti-glare



**WH0401**  
 Honeycomb louvre  
 built into the lighting fixture  
 Order together with the lighting fixture.

L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.