DATASHEET

Made in Italy


04/11/2026 Rev. 08/2024

Kora 1.0, code: KR1010105MB

Suspended for indoor applications

kg 0,68 IP40





DESCRIPTION

pendant for indoor applications; surface mounted (ceiling) with ceiling rose; Power consumption: 3,5W; Power supply: 230Vac; Lumen output at source: 184 lm (3000K); Delivered lumen output: 120 lm (3000K, 35°); 1 power LED, 1/4 ANSI BIN, 50 000h L90 B10 (Ta 25°C); LED colour: 3000K; Optics: 35°; CRI Colour Rendering Index: 80; Body material: body in anticorodal aluminium, ceiling rose in steel; Finishes: white (RAL 9003); RAL finish on request; built-in power supply unit; includes 2.50 m PVC cable, FROR 2x0.75 Ø5.4 mm; Ingress protection: IP40; Design by: Cibicworkshop; Operating temperature: 0°C — +45°C; Photobiological safety: photobiological safety: risk group 1 according to EN 62471:2006; Appliance class: class II; Weight: 680 g; Dimensions: Ø30x380 mm; Energy efficiency class: F (light source) in accordance with EU 2019/2015; tested and approved via E.O.L. (End Of Line) test with functioning test and check of electrical power consumption


Status: Available

ELECTRICAL CHARACTERISTICS	
Power consumption	3,5W
Power supply	230Vac
Power supply unit	built-in power supply unit
LIGHTING CHARACTERISTICS	
Number and type of LED	1 power LED
Average LED life	50 000h L90 B10 (Ta 25°C)
LED colour	3000K
CRI Colour Rendering Index	80
Binning	1/4 ANSI BIN
Optics	35°
Lumen output at source	184 lm (3000K)
Delivered lumen output	120 lm (3000K, 35°)
MECHANICAL CHARACTERISTICS	
Dimensions	Ø30x380 mm
Weight	680 g
Finishes	white RAL 9003
Mounting	with ceiling rose
Body material	body in anticorodal aluminium, ceiling rose in steel
GENERAL CHARACTERISTICS	
Ingress protection	IP40
Operating temperature	0°C — +45°C
Energy efficiency class	F (light source) in accordance with EU 2019/2015
Appliance class	class II
Walkover	no
Drive-over	no
Power cables	includes 2.50 m PVC cable, FROR 2x0.75 Ø5.4 mm
Photobiological safety	photobiological safety: risk group 1 according to EN 62471:2006

PHOTOMETRIC DATA

M - 35°

H (m)	∅ (m)	Lux max (3000K) 3.5W
0.50	0.32	1221
1.00	0.64	305
1.50	0.95	136
2.00	1.27	76
2.50	1.59	49
3.00	1.91	34



L&L Luce&Light SRL reserves the right to change the information contained in this document at any time without prior notice being given.