




TLR 01

433.92 MHz radio receiver, one-/two-channel rolling code



FREQUENCY:	433.90 MHz
POWER SUPPLY:	12÷24 Vdc
RANGE:	30 m; with antenna 100 m
CHANNELS:	2 channels
RELAY CONTACT:	1A / 24Vdc
OPERATING TEMP:	-20°C to +70°C
CONSUMPTION AT REST:	10 mA
CONSUMPTION W. 1CH:	42 mA
CONSUMPTION W. 2CH:	66 mA

TLR 01

433.92 MHz radio receiver, one-/two-channel rolling code, in plastic box with terminal box for series wiring. The internal memory can memorize up to 512 rolling code transmitters.

For good reception, we recommend installing the antenna away from metallic masses and avoiding positioning multiple receivers close together.



TLA 01

Antenna for external installation complete with mounting kit and 5-m cable. May be used if the reception of the TLC03 receiver is poor.


TLR 01 - TLA 01

Scheda Tecnica - *Data Sheet*



TLR 01

Radioricevitore 433.92 MHz mono/bicanale rolling code



FREQUENZA:	433.90 MHz
ALIMENTAZIONE:	12÷24 Vdc
PORTATA:	30 m; con antenna 100 m
CANALI:	2 canali
CONTATTO RELE':	1A / 24Vdc
TEMP. FUNZIONAMENTO:	-20°C ÷ +70°C
CONSUMO A RIPOSO:	10 mA
CONSUMO 1CH:	42 mA
CONSUMO 2CH:	66 mA

TLR 01

Radioricevitore 433.92 MHz mono/bicanale rolling code in box plastico con morsettiera. La memoria interna può memorizzare un massimo di 512 trasmettitori rolling code.

Per una buona ricezione si consiglia di installare l'antenna lontano da masse metalliche e di evitare il posizionamento ravvicinato di più ricevitori.



TLA 01

Antenna per montaggio esterno completa di kit di fissaggio e cavo da 5 m.
Utilizzabile nei casi di scarsa ricezione del ricevitore TLC03.