



GOCCIA

OUTDOOR RECESSED



GOCCIA 2.0

max 2W max 500mA



GOCCIA 2.6

2W 24Vdc



GOCCIA 2.1


max 2W max 500mA



GOCCIA 2.7

2W 24Vdc

GOCCIA





GOCCIA 2.0

GOCCIA 2.1



Installation flush
with ground level



Ø 45 mm
H 35 mm

Ø 45 mm
H 35 mm




| | |
|----------------------------------|---|
| POWER / POWER SUPPLY CODE | max 3W max 350mA GA2031 6 D A V |
| LED COLOUR | RGB |
| OPTICS | diffuse |
| LUMEN OUTPUT AT SOURCE | 72 lm, R: 22 lm G: 40 lm B: 10 lm (350mA) |
| DELIVERED LUMEN OUTPUT | 36 lm, R: 13 lm G: 17 lm B: 6 lm (350mA) |
| NO. AND TYPE OF LEDS | 1 full-colour LED |
| MATERIAL | body in anodized aluminium screen in sandblasted extra-clear glass |
| POWER SUPPLY UNIT | not included, see p. 180 e 668 |
| POWER CABLES | includes 1.5 m FEP+RUB cable (equivalent to H05RN-F) 6x0.50/0.50 Ø6.3 mm |
| WIRING | series |
| MOUNTING | recessed (wall, ground) |
| ACCESSORIES | see p. 180 |
| NOTES | outer casing available in non-standard sizes on request |

| | |
|----------------------------------|---|
| POWER / POWER SUPPLY CODE | max 3W max 350mA GA2131 6 D A V |
| LED COLOUR | RGB |
| OPTICS | diffuse |
| LUMEN OUTPUT AT SOURCE | 72 lm, R: 22 lm G: 40 lm B: 10 lm (350mA) |
| DELIVERED LUMEN OUTPUT | 36 lm, R: 13 lm G: 17 lm B: 6 lm (350mA) |
| NO. AND TYPE OF LEDS | 1 full-colour LED |
| MATERIAL | body in anodized aluminium screen in sandblasted extra-clear glass |
| POWER SUPPLY UNIT | not included, see p. 180 e 668 |
| POWER CABLES | includes 1.5 m FEP+RUB cable (equivalent to H05RN-F) 6x0.50/0.50 Ø6.3 mm |
| WIRING | series |
| MOUNTING | recessed (wall, ground) |
| ACCESSORIES | see p. 180 |
| NOTES | outer casing available in non-standard sizes on request |



GOCCIA 2.6



Ø 45 mm
H 35 mm

CE, RoHS, III, kg 500, kg 0.15, IP67, IK10
A, A+, A++, IPS, T max 40°C

2W 24Vdc
GA2600 ■ D V

■ F - 2700K
5 - 3000K
9 - 4000K
1 - blue

diffuse

204 lm (3000K)

74 lm (3000K)

1 power LED

body in anodized aluminium
screen in sandblasted extra-clear glass

not included, see p. 180

includes 1.5 m neoprene cable
H05RN-F 2x0.35/0.75 Ø6.3 mm

parallel


recessed (wall, ground)

see p. 180

outer casing available in non-standard sizes on request



GOCCIA 2.7



Ø 45 mm
H 35 mm

CE, RoHS, III, kg 500, kg 0.15, IP67, IK10
A, A+, A++, IPS, T max 40°C

2W 24Vdc
GA2700 ■ D V

■ F - 2700K
5 - 3000K
9 - 4000K
1 - blue

diffuse

204 lm (3000K)

74 lm (3000K)

1 power LED

body in anodized aluminium
screen in sandblasted extra-clear glass

not included, see p. 180

includes 1.5 m neoprene cable
H05RN-F 2x0.35/0.75 Ø6.3 mm

parallel



recessed (wall, ground)

see p. 180

outer casing available in non-standard sizes on request

GOCCIA

ACCESSORIES AND POWER SUPPLY UNITS

| | GOCCIA 2.0 | GOCCIA 2.1 | GOCCIA 2.6 | GOCCIA 2.7 |
|--|------------|------------|------------|------------|
| ACCESSORIES FOR INSTALLATION | | | | |
|  <p>Outer casing</p> | WC0400 | | WC0400 | |
|  <p>Outer casing</p> | | WC0401 | | WC0401 |

POWER CABLES

FEP+RUB cables
(equivalent to H05RN-F)
6x0.50/0.50 Ø6.3 mm
IPS

WF7305 - 5 m
WF7310 - 10 m
WF7315 - 15 m
WF7320 - 20 m
(Goccia 2.0 / 2.1)

Neoprene cables
H05RN-F 2x0.35/0.75 Ø6.3 mm
IPS

WF5205 - 5 m
WF5210 - 10 m
WF5215 - 15 m
WF5220 - 20 m
(Goccia 2.6 / 2.7)

order together with the lighting fixture

POWER SUPPLY UNITS Goccia 2.0 / 2.1

350mA

| Max no. fixtures | PSU | IP | Page |
|------------------|----------------|----|---------|
| - | RGB controller | - | 679-684 |

POWER SUPPLY UNITS Goccia 2.6 / 2.7

| Max no. fixtures | PSU | IP | Page |
|------------------|-------|----|------|
| 1...n | 24Vdc | 20 | 671 |
| 1...n | 24Vdc | 67 | 671 |

GOCCIA

PHOTOMETRIC DATA

GOCCIA 2.6
2.7

D - Diffuse

