




GOCCIA


OUTDOOR STEP LIGHTS
ORIENTATION LIGHT



diffuse



RGB



2700K 3000K 4000K blue

ROUND COVER



GOCCIA 2.0 p. 380
constant current
max 3W max 350mA



GOCCIA 2.6 p. 381
constant voltage
2W 24Vdc

SQUARE COVER



GOCCIA 2.1 p. 380
constant current
max 3W max 350mA



GOCCIA 2.7 p. 381
constant voltage
2W 24Vdc






GOCCIA



GOCCIA 2.0



GOCCIA 2.1



Ø 45 mm
H 35 mm

Ø 45 mm
H 35 mm

POWER / POWER SUPPLY CODE	max 3W max 350mA GA2031 6 D A V - ■
LED COLOUR	RGB

POWER / POWER SUPPLY CODE	max 3W max 350mA GA2131 6 D A V - ■
LED COLOUR	RGB

POWER CABLES	includes 1.5 m FEP+RUB cable (equivalent to H05RN-F) 6x0.50/0.50 Ø6.3 mm 1 - 5 m 2 - 10 m 3 - 15 m 4 - 20 m
---------------------	---


POWER CABLES	includes 1.5 m FEP+RUB cable (equivalent to H05RN-F) 6x0.50/0.50 Ø6.3 mm 1 - 5 m 2 - 10 m 3 - 15 m 4 - 20 m
---------------------	---

OPTICS	diffuse
LUMEN OUTPUT AT SOURCE	72 lm, R: 22 lm G: 40 lm B: 10 lm (350mA)
DELIVERED LUMEN OUTPUT	36 lm, R: 13 lm G: 17 lm B: 6 lm (350mA)
NO. AND TYPE OF LED	1 full-colour LED 50000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized aluminium screen in sandblasted extra-clear glass
POWER SUPPLY UNIT	not included, see p. 382 and 844
WIRING	series
MOUNTING	recessed (wall, ground)
ACCESSORIES	see p. 382
NOTES	outer casing available in non-standard sizes on request
PHOTOMETRIC DATA	

OPTICS	diffuse
LUMEN OUTPUT AT SOURCE	72 lm, R: 22 lm G: 40 lm B: 10 lm (350mA)
DELIVERED LUMEN OUTPUT	36 lm, R: 13 lm G: 17 lm B: 6 lm (350mA)
NO. AND TYPE OF LED	1 full-colour LED 50000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized aluminium screen in sandblasted extra-clear glass
POWER SUPPLY UNIT	not included, see p. 382 and 844
WIRING	series
MOUNTING	recessed (wall, ground)
ACCESSORIES	see p. 382
NOTES	outer casing available in non-standard sizes on request
PHOTOMETRIC DATA	



GOCCIA 2.6



Ø 45 mm
H 35 mm

CE, LED, III, kg 500, kg 0.20, IP67, IK10
A, A+, A++, IPS, T max 40°C

2W 24Vdc

GA2600 ■ D V - ■

■ F - 2700K
5 - 3000K
9 - 4000K
1 - blue

■ includes 1.5 m neoprene cable
H05RN-F 2x0.35/0.75 Ø6.3 mm
1 - 5 m
2 - 10 m
3 - 15 m
4 - 20 m

diffuse

204 lm (3000K)

74 lm (3000K)

1 power LED
3-step MacAdam (white LED colour)
50000h L90 B10 (T_a 25°C)

body in anodized aluminium
screen in sandblasted extra-clear glass

not included, see p. 382

parallel

recessed (wall, ground)


see p. 382

outer casing available in non-standard
sizes on request

see p. 770



GOCCIA 2.7



Ø 45 mm
H 35 mm

CE, LED, III, kg 500, kg 0.20, IP67, IK10
A, A+, A++, IPS, T max 40°C

2W 24Vdc

GA2700 ■ D V - ■

■ F - 2700K
5 - 3000K
9 - 4000K
1 - blue

■ includes 1.5 m neoprene cable
H05RN-F 2x0.35/0.75 Ø6.3 mm
1 - 5 m
2 - 10 m
3 - 15 m
4 - 20 m

diffuse

204 lm (3000K)

74 lm (3000K)

1 power LED
3-step MacAdam (white LED colour)
50000h L90 B10 (T_a 25°C)

body in anodized aluminium
screen in sandblasted extra-clear glass

not included, see p. 382

parallel

recessed (wall, ground)



see p. 382

outer casing available in non-standard
sizes on request

see p. 770

GOCCIA

ACCESSORIES AND POWER SUPPLY UNITS

	GOCCIA 2.0	GOCCIA 2.1	GOCCIA 2.6	GOCCIA 2.7
ACCESSORIES FOR INSTALLATION				
 <p>Outer casing</p>	WC0400		WC0400	
 <p>Outer casing</p>		WC0401		WC0401

POWER CABLES

the choice of power cable is included in the configuration of the code for the lighting fixture

- 1 length 5 m
- 2 length 10 m
- 3 length 15 m
- 4 length 20 m

white LED colour

Neoprene cables

H05RN-F 2x0.35/0.75 Ø6.3 mm IPS

RGB

FEP+RUB cables (equivalent to H05RN-F)

6x0.50/0.50 Ø6.3 mm IPS

POWER SUPPLY UNITS Goccia 2.0 / 2.1

Max no. fixtures	PSU	IP	Page
-	RGB controller	-	855 - 860

POWER SUPPLY UNITS Goccia 2.6 / 2.7

Max no. fixtures	PSU	IP	Page
1...n	24Vdc	20	847
1...n	24Vdc	67	847

GOCCIA 2.7 >
customized version with 3500K LED colour, 2W

Project by / Architecture & Urbanisme 21

Yvone Schiltz et Associés /

Parallel architecture intérieur /

Agence Christophe Gontrand & Associés

Light planning by / Distylight

Groupe Foyer Headquarters, Leudelange, Luxembourg



GOCCIA

OUTDOOR STEP LIGHTS

GOCCIA 2.6
2.7

D - Diffuse

