
ICE LED

OUTDOOR STEP LIGHTS LIGHT POINT FOR GARDENS AND FLOWERBEDS


Surface	$\begin{bmatrix} 40 \\ 40 \\ 40 \end{bmatrix} \begin{bmatrix} 40 \\ 51 \end{bmatrix}$		
Installation flush with ground		ICE	LED 1.1
	C∈ III ⊕ ⊕ ™ № 500		
	© kg 0.24 IP67 IK07		△ kg 0.40 IP67 IK07
	A A+ A++ CPS CASAMBI (T max 40°C		A A+ A++ (CPS) CASAMBI (T max 40°C)
POWER / POWER SUPPLY CODE	max 1W max 350mA LE1011 – D A V - –		max 1W max 350mA LE1111 D A V -
	F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue		F - 2700K 5 - 3000K 9 - 4000K 0 - 5000K 1 - blue
POWER CABLES	includes 1.5 m neoprene cable H05RNF 2x0.35/0.75 Ø6.3 mm 1 - 5 m 2 - 10 m 3 - 15 m 4 - 20 m		includes 1.5 m neoprene cable H05RN-F 2x0.35/0.75 Ø6.3 mm 1 - 5 m 2 - 10 m 3 - 15 m 4 - 20 m
OPTICS	diffuse		diffuse
lumen output at source	110 lm (3000K, 350mA)		110 lm (3000K, 350mA)
DELIVERED LUMEN OUTPUT	89 lm (3000K, 350mA)		89 lm (3000K, 350mA)
NO. AND TYPE OF LED	1 power LED 1/4 ANSI BIN (white LED colour) 50000h L90 B10 (Ta 25°C)		1 power LED 1/4 ANSI BIN (white LED colour) 50000h L90 B10 (Ta 25°C)
MATERIAL	body in anodized aluminium and sandblasted glass		body in anodized aluminium and sandblasted glass
POWER SUPPLY UNIT	not included, see p. 904		not included, see p. 904
WIRING	series		series
MOUNTING	recessed (wall, ground) surface mounted (ground)		recessed (wall, ground) surface mounted (ground)
ACCESSORIES	see p. 451		see p. 451
NOTES	certified ETL version available on request		certified ETL version available on request
PHOTOMETRIC DATA	see p. 836		see p. 836



ACCESSORIES FOR INSTALLATION



WC0410 Outer casing (Ice LED 1.0)



WC0411 Outer casing (Ice LED 1.1)

ICE LED

OUTDOOR STEP LIGHTS

ICE LED 1.0 1.1

D--Diffusso / Diffuse

